



LD1.0 LITE

The LD1.0 LITE is a new amplifier of class D loop amplifier. The drive offers essential features (AGC, compressor, integrated power supply) to cover installation in rooms up to 180m².

Due to the high-efficiency Class D technology, the amplifier has less power consumption and natural cooling. It guarantees outstanding sound quality without clipping or distortion.



Mounting accessories

OP-R	Mounting kit for support 1 or 2 amplifiers
RC	Copper strip designed for induction loops
C10-RC	RC copper foil terminal block

Specifications

INPUT

Audio inputs	2 inputs : 1 line + 1 mic
Type	2 and 3 pts Phoenix connector
Sensitivity	-50 dB microphone, -10 dB line

POWER SUPPLY

Type	Integrated
Voltage	115/230 V (automatic) 50/60 Hz
Max power consumption	200 VA
Consumption	6 W

LD1.0 LITE

AUDIO FEATURES	
Automatic Gain Control	AGC optimized for Dynamic speech > 36 dB
Frequency bandwidth	80 Hz to 9,5 kHz at -3dB
OUTPUT	
Loop impedance	0.5 Ω to 3 Ω
Output voltage	34 Vrms
Peak current	8A
RMS current	4Arms
Additional features	
Fault verification	Protect LED Display : Current too high – Open loop – Thermal protection
Cooling	Natural cooling
IP class	IP 20
Dimensions (MM)	
H x L x D	42 x 200 x 215 mm
Weight (with bow)	1.5 Kg (1.9 Kg)
5 years warranty	
EN60118-4 Standard	
Pictures	

