

OP-6515HK

OP-6515HK is a full-duplex system designed to improve communication at fixed-screen counters. Incorporating a DSP, it is particularly effective when communications are impaired by the presence of double-glazing, security screens or other counter security systems.

Thanks to its wireless loudspeaker client side, you save time (no more drilling) and avoid vandalism on the cable!



Product references

OP-6515H	Digital countertop intercom with touch-sensitive keypad, customer-side wireless loudspeaker
OP-6515HB	Digital countertop intercom with touch-sensitive keypad, customer-side wireless loudspeaker and induction loop driver
OP-6515HBK	Digital countertop intercom with touch-sensitive keypad, customer-side wireless loudspeaker, induction loop driver and headset HD-1022
OP-6515HK	Digital countertop intercom with touch-sensitive keypad, wireless customer speaker and headset HD-1022

Specifications

Agent microphone	Ultra directional ; built in speaker : 3W at 8Ω
Speaker-Microphone (customer side)	Built in mic : -46dB Uni-directional ; Built in speaker: 1W at 4Ω
Power supply voltage	DC 12V ≤ 5W
Operating temperature and humidity	-20°C ~ +70°C, < 90% RH (no condensation)

AUDIO

Voice reception delay	No delay
Audio coding	PCM/AAC
Speaker unit	4Ω 3W Speaker
Signal-to-noise ratio	≥ 90dB
Bandwidth	20Hz ~ 16kHz
Sampling	8kHz ~ 32kHz

Dimensions (MM)

Agent-side microphone	160 x 95 x 46,5 mm
Weight	0,55 Kg
Microphone speaker	85 x 25 mm
Weight	0,15 Kg

OP-6515HK

Pictures



Variant products

OP-6515H



OP-6515HB



OP-6515HBK

